

PRODUCT SPECIFICATION



Part No.: SRC-13G45GB-520GK
Ceramic LED


TABLE OF CONTENTS

1. Product Features.....	P2
2. Mechanical Dimensions	P2
3. Absolute Maximum Rating	P3
4. Optical Character	P3
5. Optical Character Curves	P4
6. Spectrum Curves	P5
7. Viewing Angle Curves.....	P5
8. Storage & Packaging	P6

1. Product Features

- High-Luminosity Green LED
- Clear Silicone Dome Lens
- Viewing Angle: 120 °
- Die Material: InGaN
- Low Voltage DC Operated
- Board Material: Aluminum

2. Mechanical Dimensions



Notes:

1. Dimensions in millimeters (mm)
2. Dimension Tolerance: ± 0.1 mm

3. Absolute Maximum Rating @ Ta = 25 °C

Parameter	Symbol	Maximum Rating	Unit
Continuous Forward Current	IF	700	mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	IFP	1000	mA
Reverse Voltage	VR	5	V
Power Dissipation	PD	3	W
Electrostatic Discharge	ESD	1000	V
Operating Temperature Range	TOPR	-25°C to +60°C	
Storage Temperature Range	TSTG	-35°C to +80°C	
Lead Soldering Temperature	TSOL	260°C	

4. Optical Character @ Ta = 25 °C

Parameter	Symbol	Color	Min.	Typ.	Max.	Unit	Test Condition
Forward Voltage	VF	G	3.2	3.4	3.6	V	IF=700mA
Luminous Flux	Φ	G	160	170	180	lm	IF=700mA
Wavelength	WL	G	520	522.5	525	nm	IF=700mA
Reverse Current	IR		0		10	μA	VR=5V
Viewing Angle	2θ _{1/2}				120	deg	IF=700mA
Recommend Forward Current	IF (typ)	G			700	mA	


Notes:

Forward Voltage Tolerance: ± 0.1 V


5. Optical Character Curves

(Unless otherwise specified, all values are measured at 25 °C ambient temperature)


Forward Current vs. Forward Voltage
T_c=25C




Forward Current vs. Relative Luminous Flux
T_c=25C




Case Temperature vs. Forward Voltage
I_f=700mA



Case Temperature vs. Relative Luminous Flux
I_f=700mA




6. Spectrum Curves



7. Viewing Angle Curves

Radiation Characteristic


IF=700mA



8. Storage & Packaging

Storage & Handling Instructions for Unpacked LED Beads:

1. Immediate Use: Unpacked LED beads are recommended to be soldered within one day.
2. Short-Term Storage (Within 1 week): If not used immediately, re-vacuum seal and store in an environment with a temperature of 20-35 °C and 30-60% relative humidity. If re-vacuum sealing is not possible, store the LED beads in a moisture-proof box, maintaining 25 ± 3 °C and 50-60% humidity.



Notes:

1. Quantity: 20pcs/tube
2. Dimensions in millimeters (mm)
3. Dimension Tolerance: ± 0.2 mm